

## Dodge Omni | 1980-1990 Car Radio Removal



**STEP 1:**

Locate and remove (2) two phillips screws securing the top of the radio dash panel. Locate and remove (2) two phillips screws securing the bottom of the dash.



**STEP 2:**

The radio dash panel is now free to be removed. The left side of this dash is partially wedged behind the steering column assembly. Pull to free the right side of the dash then slide the dash to the right to free the part of the dash wedged behind the steering column assembly.



**STEP 3:**

The radio is held in with two (2) 10 mm bolts. Remove the upper right bolt. The second bolt at the lower left of the radio is partially obstructed by the ashtray dash panel. The ashtray dash panel must be loosened and pulled away slightly in order to have access to this obstructed bolt. (occasionally you might have access to the bolt without moving the lower dash panel)



**STEP 4:**

Remove the ashtray below the radio. Locate and remove two (2) phillips screws visible once the ashtray is removed.



**STEP 5:**

Locate and remove one (1) phillips screw on EACH SIDE securing the bottom of the center dash panel near the floor. The center dash panel can now be moved just enough to gain access to the obstructed 10 mm bolt securing the radio. Pull gently outward on the UPPER part of the center dash assembly near the ashtray. Pulling the upper part of the center dash panel will pull the dash panel far enough away to have access to the 10 mm bolt.



**STEP 6:**

Once you remove both bolts securing the radio, pull the radio out of the dash. Unplug the cable plugged into the rear of the radio. Unplug both connectors attached to the rear of the radio. There will also be a metal braid strap secured to the rear of the radio with a 10 mm bolt. Remove the 10 mm bolt and you should be able to completely remove the radio from the dash. DO NOT CUT THIS BRAIDED STRAP.