

# Nissan Pathfinder | 1997-2000

## Car Radio Removal



### STEP 1:

The plastic dash panel surrounding the radio and air conditioner controls must be removed before removing the radio.

Locate and remove two (2) phillips screws located on the bottom of the plastic dash panel. (these screws will not be visible unless you look up at the bottom of the plastic panel)



### STEP 2:

When both screws have been removed, the dash can then be unsnapped from the main dash.

Pull the bottom of the dash until the dash panel begins to unsnap, then continue up the panel until the plastic panel has separated from the main dash.

Unplug 2 connectors attached to the rear of the cigarette lighter. Unplug 2 connectors from the rear of the hazard and defrost switches. (if your vehicle has a rear window wiper switch on the lower left of the plastic dash panel, you can swing the dash panel off to the left so you can gain access to the radio - as seen in the photo above)



### STEP 3:

Once the plastic panel is removed, the radio and screws securing the radio can now be seen.

The radio is secured to the pocket below the radio by metal brackets on each side of the radio/pocket assembly. To remove the radio/pocket assembly locate and remove four (4) phillips screws, 2 on each side of the radio/pocket assembly.

Once the screws are removed, pull the radio/pocket assembly out of the dash.

Unplug 2 white connectors plugged into the rear of the radio. Unplug the single black cable plugged into the rear of the radio.

Once all connectors have been unplugged, pull the radio/pocket assembly completely out of the dash.