

# Oldsmobile Cutlas Supreme | 1993 Car Radio Removal



**STEP 1:**

Locate and remove five (5) phillips screws that secure the top of the plastic panel that surrounds the radio. These screws are located above the dash instruments.



**STEP 2:**

Once the screws have been removed, the entire plastic dash panel can be pulled from the main dash assembly. The best place to start is the top right corner above the radio. With your hands, pull the dash until it begins to separate from the main dash assembly.



**STEP 3:**

Continue to pull the dash until the left side unsnaps from the main dash assembly. The left side of the dash contains the headlight switch which will prevent you from completely removing the dash panel.



**STEP 4:**

The plastic dash panel can be set up on top of the main dash assembly as seen in the photo above. There should be enough wiring attached to the headlight switch to allow you to set the plastic dash panel on top of the main dash assembly.

The radio should now be visible.



**STEP 5:**

The radio is secured to the dash by a bracket attached to the bottom of the radio. This bracket is screwed into the dash with two (2) 7 mm bolt screws.

Locate and remove both screws. The radio can now be pulled out of the dash.

Pull the radio out of the dash. Unplug the black cable plugged into the rear of the radio. Unplug the plastic wire harness connector from the rear of the radio.

**Note:** You will need the bracket attached to the bottom of the GM radio when installing the new radio.