

Dodge Ram 1500/2500/3500 | 1994-1996 Car Radio Removal



STEP 1:

To remove the radio, the entire plastic dash panel surrounding the radio and dash instruments must be removed.

Pull out the ashtray. Locate and remove two (2) phillips screws securing the ashtray bracket. Pull out the ashtray bracket and set it aside.



STEP 2:

Open the drink tray. Locate and remove two (2) phillips screws hidden behind the front panel of the drink tray. Once the screws are removed, pull out the entire drink tray assembly and set it aside.

Dodge Ram 1500/2500/3500 | 1994-1996 Car Radio Removal



STEP 3:

Once the screws securing the ashtray bracket and drink tray assembly have been removed, the entire dash panel can be removed.

The dash panel simply unsnaps from the dash. Start at the top of the dash at one corner and pull gently until the dash separates from the body of the main dash.



STEP 4:

The radio is secured to the dash with two (2) 10mm bolts. Locate and remove both.



STEP 5:

Pull the radio out of the dash. Unplug the black cable plugged into the rear of the radio. Unplug two plastic wire harness connectors (1 black, 1 gray) snapped into the rear of the radio. Some years of this vehicle have a metal braid bolted to the rear of the radio. Remove the braid by removing the 10mm bolts that secures it to the rear of the radio.