

Honda Prelude | 1992-1995

Car Radio Removal



NOTE 1:

The Honda radio in this vehicle is attached as one unit to the pocket below the radio. The radio/pocket assembly is secured to the dash by (2) phillips screws / 8mm bolts attached to the rear of the radio. To access these screws, the center console dash panel must be removed first.



NOTE 2:

The center console dash panel must be removed in order to remove the Honda radio in this vehicle. The center console dash panel is secured to the body of the dash with (4) phillips screws on each side of the dash, and (2) phillips screws at the top of the dash just above the radio.



NOTE 3:

If you have a standard or stick shift:

The stick shift knob must be removed. Pull down hard on the top of the leather boot cover surrounding the stick shift. Once the leather is pull down, the stick shift knob simply unscrews.



STEP 1:

Locate and remove four (4) phillips screws on each side of the center console dash panel. Locate and remove two (2) phillips screws at the top of the center console dash panel between the top of the radio and the bottom of the air conditioner controls.



STEP 2:

Once all screws have been removed, pull the center console dash panel up and away from the radio.



STEP 3:

Once the center console dash panel has been removed, the radio and mounting brackets for the radio can be seen.

The radio/pocket assembly is attached to the plastic housing surrounding the radio/pocket assembly. You are going to remove the entire plastic assembly along with the radio as one whole unit. Locate and remove four (4) phillips screws, (2) on each side of the radio.

Honda Prelude | 1992-1995 Car Radio Removal



STEP 4:

Once all (4) screws have been removed, pull the entire unit out of the dash. Unplug the connector attached to the rear of the cigarette lighter. Unplug the black cable plugged into the rear of the radio. Unplug the plastic white wire harness connector plugged into the rear of radio. Move to STEP 5 to remove the Honda radio/pocket assembly from the radio housing.



STEP 5:

As mentioned earlier, the radio/pocket assembly is attached to the radio housing with (2) phillips screws / 8mm bolts at the rear of the radio. Remove the screws. Once the screws are removed, slide the radio/pocket assembly out through the front of the radio housing.

The radio housing frame should look like the photo above with the radio removed.