

Jeep Wrangler | 1997-1999

Car Radio Removal



STEP 1:

To remove the radio, the plastic center dash panel surrounding the radio and air conditioner controls must be removed from the main body of the vehicles dash.

This panel is secured at the very top by 2 phillips screws and at the bottom by 1 phillips screw located behind the ashtray.



STEP 2:

Locate a long, narrow plastic panel at the top of the dash and base of the windshield. This plastic panel unsnaps simply by lifting the panel up. With your hands, pull either the end of the panel at the drivers side or the passenger side, unsnapping the panel. (as seen in the photo above)



STEP 3:

In the center of the dash, on the upper part of the radios plastic center dash panel are two (2) phillips screws that were hidden underneath the long, narrow plastic panel just removed. Remove both screws.



STEP 4:

Open the ashtray and remove it by pressing down the tab at the top of the ashtray. Located behind the ashtray is one (1) phillips screw. Remove the screw.



STEP 5:

Once all screws have been removed, the center dash panel can then be removed. Pull the dash panel and it will unsnap from the main body of the dash. The radio and two (2) bolts securing the radio should now be visible. Locate and remove two (2) 10mm bolts securing the radio.



STEP 6:

Pull the radio out of the dash. Unplug (1) black and (1) gray connector from the rear of the radio. Unplug the antenna cable from the rear of the radio. A metal braid strap will be secured to the rear of the radio with a 10mm bolt. Remove the bolt and the radio can now be completely removed from the dash.