

Saturn | 1991-1994 Car Radio Removal



STEP 1:

Unsnap one of the lower plastic dash panels on either side of the radio. The plastic dash panels are secured to the dash assembly with 2 snaps at the top of the panel.



STEP 2:

Reach your hand behind the bottom of the plastic dash panel (seen in the photo above behind the cigarette lighter opening). Gently pull the lower part of the plastic dash panel until it begins to unsnap from the main dash assembly.



STEP 3:

Move to the top of the plastic dash panel and continue to unsnap the panel.

Note: the air conditioner vents are designed to separate from the rear of the plastic dash panel and may remain in the dash when the dash panel is pull away.



STEP 4:

The radio is secured to the dash with a metal bracket attached to the top of the radio. This bracket is secured to the dash with two (2) 7 mm bolts/screws.

Remove both screws.



STEP 5:

Pull the radio out of the dash. Unplug the black cable from the rear of the radio. Unplug the plastic connector from the rear of the radio. The radio can now be completely removed from the dash.



If the air conditioner vents unsnapped from the plastic dash panel and remained in the dash:

Pull the air vents out of the dash. The air vents have tabs that snap into the rear of the plastic dash panel.

To Start, line up and attach the snaps at the bottom of the air conditioner vents. Once the snaps at the bottom are aligned and secured, snap the top of the vent into the dash panel.