

Toyota Celica | 1994-1995 Car Radio Removal



STEP 1:

Insert the tip of a small flat head screwdriver between the plastic dash panel surrounding the gear shift area and the body of the center dash. Gently pry the plastic dash panel up to unsnap it from the body of the center dash. With your hands pull the plastic dash panel and unsnap it completely from the body of the center dash assembly. Set the plastic dash panel aside away from the dash.



STEP 2:

Hidden behind the plastic dash panel just removed are two (2) phillips screws securing the bottom of the plastic dash panel surrounding the radio and air conditioner controls. Locate and remove both phillips screws.

STEP 3:

Once the screws securing the bottom of the dash panel have been removed, the top of the plastic dash panel can then be unsnapped from the dash. With your hands, gently pull the dash panel until it unsnaps completely from the dash. Pull the plastic dash panel and move it aside. There will be wires and connectors attached to the rear of the plastic dash panel. You do NOT need to disconnect these connectors. As seen in the photo above, there will be enough slack in the wires to allow you to pull the dash panel and set it off to the side, away from the radio.

The radio and the screws securing the radio should now be visible. The radio and pocket below the radio are attached together by metal brackets on each side of the radio. Locate and remove four (4) phillips screws securing the brackets attached to the sides of the radio/pocket assembly. Pull the radio/pocket assembly to remove it from the dash.

Unplug the antenna cable from the rear of the radio. Disconnect 2 white connectors from the rear of the radio. The radio/pocket assembly can now be completely removed from the dash.