

Toyota Paseo | 1991-1995 Car Radio Removal



STEP 1:

The radio is secured to the frame of the vehicles dash with screws located behind the plastic dash panel surrounding the radio.

This plastic dash panel unsnaps from the body of the vehicles dash.



STEP 2:

The bottom of the plastic dash panel, just below the bottom of the pull out cup holder, can be lifted up. With your fingers, gently pull one of the lower corners, followed by the other to free the lower part of the plastic dash panel from the body of the vehicles dash. To remove the top of the plastic dash panel, pull the dash panel down to free the tabs at the top of the panel that are hidden behind main dash assembly.



STEP 3:

Unplug the white connector attached to the defrost switch. Pull the plastic dash panel away from the dash.

The radio is now visible. The radio is attached to metal brackets as one piece with the pocket/tray, ashtray, and pull out cup holder. To remove the entire assembly, remove four (4) phillips screws / 8mm bolts that secure the metal brackets to the dash. Once the phillips screws / 8mm bolts have been removed, pull the entire radio/pocket/cup holder assembly from the dash.



STEP 4:

Unplug the antenna cable from the rear of the radio. Unplug 2 connectors attached to the rear of the radio. Disconnect the connectors attached to the rear of the cigarette lighter.

Once all connectors have been disconnected, pull the entire radio/pocket/cup holder assembly out of the dash.